



- Four (4) Hot-swappable module slots
- One (1) Expansion Slot
- 20 Gigabit Aggregating and Routing backplane\*\*
- Dual AC or DC – 48Vdc power supplies
- Local or remote configuration available\*\*
- Modular design provides the ability to make updating your infrastructure quick, easy and inexpensive.
- Supports Copper and Fiber Environments\*
- Allows secure and easy access for all of your monitoring appliances
- High density design saves rack space and power consumption
- Reduces number of power outlet and UPS connections needed
- Helps achieve green data center status
- Chassis weight is 40% less than previous models
- Compliance to EN55022 (CISPR22) Class B
- Compliance to EN61000-4-2,3,4,6,8; ENV50204, EN55024, heavy industry level, criteria A
- MTBF 368.5K Hrs min.

\* inserted Module option.

\*\*Not available in Power only chassis.

Rear Panel (Dual AC Power Option)



Rear Panel (Dual DC Power Option)



### Technical Specs

**Environmental** Operating Temperature: 0°C to 50°C  
Storage Temperature: -20°C to 85°C  
Relative Humidity: 90% Non condensing

**Electrical** Power Input: 85-264 VAC (47-63 Hz)/  
36-72 VDC  
Power Input: 9 – 13 Watt  
Power Output: 50 Watt max.

**Dimensions** 44.05 cm x 4.4 cm x 31.63 cm  
17.33 in x 1.73 in x 12.44 in  
3.2 kg / 7.0 lbs

Web: [www.criticaltap.com](http://www.criticaltap.com)  
Email: [sales@networkcritical.com](mailto:sales@networkcritical.com)

European HQ: Network House, Southview Park, Caversham,  
Reading RG4 5AF, United Kingdom  
Tel +44 (0)118 9543210 Fax +44 (0)118 9545795

The Americas: 3675 Harlem Road, Buffalo, NY 14215  
Telephone 716-558-7280 Fax 716-568-8280



# Network Critical

Providing the MissingLINK™

## SmartNA™ Portable Chassis



- One (1) Hot-Swappable Module Slot
- Dual AC or DC - 48vdc power supplies
- Local or remote configuration
- Modular design provides the ability to make updating your infrastructure quick, easy and inexpensive.
- Easily installs anywhere in the network infrastructure.
- Supports Copper and Fiber environments
- Allows secure and easy access for all of your network appliances
- Compliance to IEC 60950-1
- Compliance to EN55022; EN61000 ,3,4 ; EN50024.
- MTBF 50k Hrs (AC)



### Technical Specs


<b>Environmental</b> Operating Temperature: 0°C to 50°C Storage Temperature: -20°C to 85°C Relative Humidity: 90% Non condensing	<b>Electrical</b> Power Input: 90-264 VAC (47-63 Hz)/ 7-60 VDC Power Input: 72 mWatt Power Output: 15 Watt max.	<b>Dimensions</b> 14.7 cm x 4.6 cm x 19.1 cm 5.8 in x 1.8 in x 7.5 in 0.6 kg / 1.4 lbs
Web: <a href="http://www.criticaltap.com">www.criticaltap.com</a> Email: <a href="mailto:sales@networkcritical.com">sales@networkcritical.com</a>	European HQ: Network House, Southview Park, Caversham, Reading RG4 5AF, United Kingdom Tel +44 (0)118 9543210 Fax +44 (0)118 9545795	The Americas: 3675 Harlem Road, Buffalo, NY 14215 Telephone 716-558-7280 Fax 716-568-8280




- Twelve (12) Hot-swappable module slots
- Three (3) Expansion Slots
- Dual AC or DC – 48Vdc power supplies
- Local or remote configuration available\*\*
- Modular design provides the ability to make updating your infrastructure quick, easy and inexpensive.
- Supports Copper and Fiber Environments\*
- Allows secure and easy access for all of your monitoring appliances
- High density design saves rack space and power consumption
- Reduces number of power outlet and UPS connections needed
- Helps achieve green data center status
- Compliance to EN55022 (CISPR22) Class B
- Compliance to EN61000-4-2,3,4,6,8; ENV50204, EN55024, heavy industry level, criteria A
- MTBF 368.5K Hrs min.

\* inserted Module option.

Rear Panel (Dual AC Power Option)



Rear Panel (Dual DC Power Option)



### Technical Specs

<b>Environmental</b> Operating Temperature: 0°C to 50°C Storage Temperature: -20°C to 85°C Relative Humidity: 90% Non condensing	<b>Electrical</b> Power Input: 90-264 VAC (47-63 Hz)/ 36-75 VDC Power Input: 9 – 16 Watt Power Output: 120 Watt max.	<b>Dimensions</b> 44.05 cm x 8.8 cm x 31.63 cm 17.33 in x 3.46 in x 12.44 in 3.2 kg / 7.0 lbs
Web: <a href="http://www.criticaltap.com">www.criticaltap.com</a> Email: <a href="mailto:sales@networkcritical.com">sales@networkcritical.com</a>	European HQ: Network House, Southview Park, Caversham, Reading RG4 5AF, United Kingdom Tel +44 (0)118 9543210 Fax +44 (0)118 9545795	The Americas: 3675 Harlem Road, Buffalo, NY 14215 Telephone 716-558-7280 Fax 716-568-8280